

CDT-2650-C II



UPDATED WITH A NEW LOW-PROFILE DESIGN

The Klipsch CDT-2650-C II maintains the core technology use of a high-quality 1" Silk Dome compression driver (tweeter) mated to an exclusive Tractrix® Horn combined with a 6.5" Polypropylene woofer in a 2-way design. Now with a new low-profile, more elegant grill it continues as an excellent choice for everything from whole house audio to surround sound use.

NEW SLIMTRIM™ GRILLE

With an all new grille, the visible frame size is reduced by 90% and grille depth is reduced by 80% over the previous design, for a more edge-to-edge consistent look that blends in with the wall more attractively. The new aluminum, paintable, magnetic grille attaches tightly and securely with ease to virtually eliminate resonant distortion.

KLIPSCH EXCLUSIVE CONTROLLED DISPERSION TECHNOLOGY® (CDT)

Klipsch horn-loaded technology increases acoustic output while significantly reducing distortion. Proprietary Controlled Dispersion Technology allows for both the symmetrical, 100° Tractrix Horn compression driver (tweeter) and woofer to be independently aimed toward the main listening area. The tweeter swivels while the woofer rotates 360° and pivots 15° in any direction. The precisely controlled dispersion of the horn-loaded tweeter assures that high frequencies are more effectively directed towards the listening area than typical amiable, broad dispersion, standard dome tweeters. This, combined with the woofer's ability to also direct more narrowly dispersed midbass frequencies, yields overall sound with more lifelike impact, greater detail and better vocal clarity.

SILK DOME COMPRESSION DRIVER (TWEETER)

Combined with the Tractrix Horn, the 1", low-resonance diaphragm works in conjunction with a precise phasing plug at the horn throat to create a very efficient driver with excellent transient response and lack of distortion.

POLYPROPYLENE WOOFER

Dense, yet lightweight, polymer cone reproduces authoritative bass.

SURE-GRIP MOUNTING DOGS

Provide even pressure against drywall for long-term installation reliability.

COMPATIBLE WITH THE KLIPSCH IK-650-C INSTALL KIT

For increased mounting flexibility and pre-install marking during new construction.

COMPATIBLE WITH THE KLIPSCH ME-650-C FIRE-RATED SPEAKER ENCLOSURE

For meeting building codes and/or reduction of transferred sound between rooms.

SPECIFICATIONS	CDT-2650-C II
Frequency Response	77Hz-20KHz ± 3dB
Sensitivity	91dB @ 2.83V / 1m
Nominal Impedance	8 ohms compatible
Crossover Frequency	3070Hz
Power Handling	50W RMS / 200W Peak
Recommended Amplifier Power	100 W
High Frequency Driver	1" (2.54cm) Silk dome tweeter mated to a swiveling 100° round Tractrix® Horn
Low Frequency Driver	6.5" (16.51cm) pivoting Polypropylene cone woofer
Enclosure Material/Type	ABS/Infinite baffle, front flush with wall
Wire Gauge Accommodated	12 ga
Diameter	9.5" (24.13cm)
Cutout Dimensions	8.3" (21.08cm)
Mounting Depth	4.5" (13.72cm)
Weight	6.6 lbs. (2.99kg)
Finish	White paintable frame and grille
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)
Built From	2012