

R-28PF



Klipsch®

REFERENCE



TURNTABLE READY



BLUETOOTH®
WIRELESS TECHNOLOGY



TV READY



PC READY



NO RECEIVER NEEDED



SIMPLE SETUP

NO RECEIVER NEEDED

The Klipsch R-28PF internal amplifier eliminates the need for an expensive, complicated, external receiver.

REFERENCE ACOUSTICS

High Efficiency/Low Distortion, Wide Dynamic Range, Flat Frequency Response and Controlled Directivity are Klipsch's acoustic principles. These speakers embrace those ideals to deliver all the power, detail and emotion you would expect from a Klipsch Reference loudspeaker, no bullshit.

SIMPLE SETUP

With a wide range of digital, analog and wireless inputs, the R-28PF allows you to hook up any audio source quickly and easily.

OPTICAL DIGITAL AUDIO

Don't want a soundbar? Hook up your TV or other digital source with the included optical cable to enjoy big sound in your living room.

TURNTABLE READY

The built-in phono pre-amp lets you enjoy your favorite records without the need for additional electronics. Simply hook up your turntable and listen.

BLUETOOTH® WIRELESS TECHNOLOGY

Works great with all Bluetooth-enabled smartphones, tablets and computers allowing you to play music directly from your device.

HIGH EFFICIENCY AMPLIFICATION WITH DIGITAL CROSSOVER

The R-28PF floorstanding speakers incorporate bi-amplified ultra low-noise amplifiers custom-designed to maximize system performance. The digital equalizer and crossover allow our engineers to extract every ounce of performance without distortion.

SUBWOOFER OUTPUT WITH BASS MANAGEMENT

Want more bass? Use the subwoofer output to connect to any powered subwoofer. Enable the subwoofer output's bass management feature to perfectly blend your speaker with your subwoofer.

REMOTE CONTROL

An easy-to-use wireless remote control included.

EASY TO READ LED DISPLAY

LED array clearly shows the active input. Don't want to see the lights? Simply press the LED button on the remote to turn off the front facing LEDs

SPECIFICATIONS

SYSTEM DESCRIPTION	Powered Floorstanding Speakers (pair)
FREQUENCY RESPONSE	33Hz - 20kHz
MAX OUTPUT	114dB @ 1M
TOTAL SYSTEM POWER	260W Total System Power (520W Peak) Bi-Amplified Tweeter: 20W per channel cont. @ <1% THD+N Woofers: 110W per channel cont. @ <1% THD+N
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm tweeter mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" (10.2cm) copper spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	1700 Hz (active)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via front-firing port
INPUTS	<ul style="list-style-type: none"> • Bluetooth® wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
HEIGHT, WIDTH, DEPTH	42" (106.6cm), 9.5" (24.1cm), 15.7" (39.8cm)
WEIGHT	56.67lbs (25.68kg)
FINISH	Brushed black polymer veneer
VOLTAGE	100V-120V / 220-240V selectable 50/60Hz internal power supply with region specific power cords
INCLUDED ACCESSORIES	<ul style="list-style-type: none"> • Remote control (with 2 x AAA batteries) • Magnetic grille • 5M speaker wire with 4-wire connector • 1.8M power cord (region specific) • 2M 3.5mm aux cable • 3M optical cable
BUILT FROM	2017

Klipsch®

KEEPERS OF THE SOUND

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM

All specifications are subject to change without notice. ©2015 Klipsch Group, Inc. Klipsch, Keepers of the Sound and Tractrix are registered trademarks of Klipsch Group, Inc. a wholly-owned subsidiary of Voxix International Corporation. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth Sig, Inc. and any use of such marks by Klipsch Group, Inc. is under license.